

Declare.

HIMACS Solid Surface LX Hausys America, Inc.

Final Assembly: Adairsville, GA, USA; Cheongju, South Korea

Life Expectancy: 60+ Year(s)

Embodied Carbon: 55.1-78.4kg CO₂eq 

Declared Unit: 1m²

End of Life Options: Salvageable/Reusable in its Entirety,
Landfill (100%)

Ingredients:

Unnamed Material: Aluminum hydroxide; Polymethyl methacrylate; Titanium dioxide; Cinquasia Red; C.I. Pigment Yellow 110; Carbon black; C.I. Pigment Blue 60; Di(2-ethylhexyl) terephthalate; C.I. Pigment Yellow 128; Methyl methacrylate; Synthetic Mica; C.I. Pigment Green 7

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

LXH-0002

EXP. 01 APR 2027

Original Issue Date: 2022