

Class 1

Seratone® AQUA PLUS®

Building Products Information Requirements | Information Sheet

Version: Seratone® AQUA PLUS® V4 17.06.25

Product name	Seratone® AQUA PLUS®
Product line	
Product identifier	Seratone® AQUA PLUS®

Product description

Seratone® AQUA PLUS® is a range of pre-finished panels designed for wet and dry areas. Panels are aesthetically pleasing and immensely practical. Applications include wall panelling, ceilings, feature walls, partitioning, kitchen splashbacks* and laundry walls.

Designed with performance in mind, Seratone® AQUA PLUS® is completely impervious, extremely durable, incredibly impact resistant and dimensionally stable. Panels will not rot, swell, or expand and contract, meaning they can be installed with complete confidence for long lasting performance in homes, hospitals, restaurants, research facilities and commercial spaces.

Seratone® AQUA PLUS® is available in a range of contemporary colours and finishes with colour matched aluminium jointers.

*Refer to Technical Installation Manual for Splashback compliance.

Key technical specifications

Seratone® AQUA PLUS® panel sizes and availability

Mineral Gloss, Mineral Matte*, Canvas Gloss, Canvas Matte, Shell Gloss & Shell

Matte: 2700 x 1200 x 4.5mm

Summit Gloss & Summit Matte: 2700 x 1200 x 4.5mm | 2400 x 1200 x 4.5mm

Polar Gloss & Polar Matte: 2700 x 1200 x 4.5mm | 2400 x 1200 x 4.5mm | 2400 x 900 x 4.5mm.

*Mineral Matte is currently not BRANZ Appraised

Note: All measurements are nominal

Weight: (8.35 kgs/m²)

2700 x 900 x 4.5mm: 18.03 kg

2400 x 1200 x 4.5mm: 24.04 kg

2700 x 1200 x 4.5mm: 27.05 kg

Relevant building code clauses

- B1 Structure — B1.3.1, B1.3.2, B1.3.3 [(a) and (j)], B1.3.4
- B2 Durability: Performance B2.3.1 (b) 15 years, and B2.3.1 (c) 5 years.
- C3 Fire affecting areas beyond the fire source — C3.4 (a)
- E3 Internal moisture — E3.3.4, E3.3.5, E3.3.6
- F2 Hazardous building materials — F2.3.1
- G3 Food preparation and prevention of contamination — G3.3.2 (a) and (b)

Contributions to compliance

BRANZ Appraisal No. 1286 - Seratone[®] will meet the durability requirements of the New Zealand Building Code (NZBC) B2/AS1 and has a serviceable life of 15 years.

Scope of use

Seratone[®] AQUA PLUS[®] is primarily for use as an internal wall and ceiling lining.

Seratone[®] AQUA PLUS[®] are suitable in wet and dry areas, such as bathrooms, open & closed shower enclosures, and laundries.

Seratone[®] AQUA PLUS[®] can also be used as a splash-back behind electric and gas hobs, specific set back distances apply.

Seratone[®] AQUA PLUS[®] has an antimicrobial additive for use in hygiene and food preparation areas.

Seratone[®] is adhesive fixed and can be installed directly to timber and steel framing, or a suitable substrate, such as plasterboard or fibre cement sheet.

Seratone[®] AQUA PLUS[®] has a range of complimentary colour matched aluminium jointer profiles. PVC jointer profiles are third party supplied through various building supply retailers.

In wet area applications all joins, including those using aluminium or PVC profiles shall be silicone sealed to create an impervious join.

Seratone[®] AQUA PLUS[®] has a Fire Material Group Number of 3

Seratone[®] AQUA PLUS[®] are not acoustically rated. Seratone[®] AQUA PLUS are not fire rated as part of a fire protected boundary or fire wall.

Conditions of use

Seratone® panels are not intended for use in exposed exterior locations.

Seratone® panels must be installed in accordance with the Seratone® Technical Installation Manual, BRANZ Appraisal No. 1286 and NZBC E3/AS1 or E3/AS2. Seratone® panels must not be subjected to submersion or continuous permanent contact with water. Do not use in saunas or steam rooms.

Some slight fading may be experienced over the course of time when exposed to direct sunlight.

Seratone® is only suitable for use between -20°C and up to a maximum of 50°C for medium or long term exposure. For short term exposure maximum temperature should not exceed ambient temperature plus 65°C.

Seratone® panels are not intended for use as a wall bracing panel.

Use of Seratone® as whiteboards may leave ghosting from some inks and is therefore not recommended.

Supporting documentation

The following additional documentation supports the above statements:

Seratone® AQUA® & Seratone® AQUA PLUS® Technical Installation Manual (Installation)	Edition 06.25	Click here
Seratone® BRANZ Appraisal No. 1286	March 2025	Click here
Seratone® Design Guide (Design)	08/24	Click here
Seratone® AQUA PLUS® Fire Test	7-595506-CV 24.12.2013	Click here
Seratone® Care & Maintenance	02. 09.24	Click here
Seratone® AQUA® & Seratone® AQUA PLUS Warranty	August 2024	Click here
Seratone® (all ranges) Formaldehyde Emissions Certificate	TR 1925148 13.07.018	Click here
Seratone® AQUA PLUS® SDS	17 June 2024	Click here

Contact details

Manufacture location	New Zealand
Legal and trading name of manufacturer	Laminex [®] New Zealand a division of Fletcher Building Products Limited
Manufacturer address for service	810 Great South Road Auckland 1061
Manufacturer website	Laminex.co.nz
Manufacturer NZBN	9429037626969
Manufacturer email	CSS@laminex.co.nz
Manufacturer phone number	0800303606

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No
