

**Class 1**
**Surround by Laminex® | FR MDF**
**Building Products Information Requirements | Info. Sheet**
**Version:** Surround by Laminex® | FR MDF | v1.2 14.09.23

<b>Product name</b>	Surround by Laminex®   FR MDF
<b>Product line</b>	N/A
<b>Product identifier</b>	Surround by Laminex®   FR MDF

**Place of manufacture**

<b>Aotearoa New Zealand</b>	
<b>Overseas</b>	✓

**Product description**

Surround by Laminex® FR MDF is designed for interior area applications and is manufactured from moisture resistant Medium Density Fibreboard (MDF).

An additive is put into to the panel during the manufacturing process to give the board Fire Resistant properties.

Each panel has one face routed with a regular decorative pattern which is pre-primed with water-based paint.

Surround by Laminex® FR MDF has a Material Group Number of 2-S.

The majority of Surround by Laminex® FR MDF panels are 12mm thick. One profile (Classic VJ 100) is 9mm thick.

All 12mm panels have a reverse flat face sealed with a white Low-Pressure Melamine (LPM). 9mm panels has a raw MDF reverse flat face.

*Note: Many FR MDF profiles are only available through an indent order. Minimum order quantity is 30 sheets (1 pack). This product is made to order and requires a longer lead time. Indent order terms and conditions apply.*

**Key technical specifications:****Surround by Laminex<sup>®</sup> FR MDF is available in one sheet size (dimensions in mm):**

- 3000(h) x 1200(w)

**Weight:**

12mm – 9.2 kg/m<sup>2</sup> | 33.12kgs

9mm - 6.9kg/m<sup>2</sup> | 24.84kgs

Surround by Laminex<sup>®</sup> FR MDF profiles run parallel with the height of the sheet (i.e. with the length of 3000(h) direction.

Surround by Laminex<sup>®</sup> FR MDF sheets use a tongue and groove joining system. Surround by Laminex<sup>®</sup> FR MDF is a grey board and comes with a pink polypropylene tongue.

*Note: All dimensions and measurements are nominal.*

**Relevant building code clauses**

- B1 Structure - B1.3.1, B1.3.2, B1.3.4, Surround by Laminex<sup>®</sup> MR MDF meets the requirements for loads arising from self-weight and impact [i.e., B1.3.3 (a) and (j)].
- B2 Durability: B2.3.1 (c) 5 years.
- C3 Fire affecting areas beyond the fire source - C3.4 (a)
- F2 Hazardous building materials - F2.3.1

**Contributions to compliance**

Surround by Laminex<sup>®</sup> FR MDF panel properties are tested in accordance with AS/NZS 4266.1:2017, AS/NZS 1580.408.2 & AS/NZS 1859.2

Surround by Laminex<sup>®</sup> FR MDF Fire test certificate and report.

**Scope of use**

Surround by Laminex<sup>®</sup> FR MDF panels must be installed in accordance with the Surround by Laminex<sup>®</sup> Fabrication and Installation Manual. This manual has been developed to allow designers, fabricators, installers and DIYers who work with Surround by Laminex to achieve performance standards for both domestic and commercial applications. Laminex<sup>®</sup> New Zealand recommend the Fabrication and Installation Manual is read and understood prior commencing installation. This publication can be downloaded at [Laminex.co.nz](http://Laminex.co.nz)

Surround by Laminex® FR MDF panels can be fixed directly to timber or steel framing, and to various substrates, including plasterboard, using a combination of adhesive and mechanical fasteners.

Surround by Laminex® FR MDF panels have a regular decorative pattern pre-primed face. Panels can be finished with a light sanding, and a minimum of two topcoats of a compatible paint in line with paint manufacturer's guidelines.

## Conditions of use

Surround by Laminex® FR MDF is intended for use as an interior wall lining panel for non-structural applications and is not intended for use in exposed exterior locations.

Surround by Laminex® FR MDF panels are **prohibited** for use in internal moisture areas.

Surround by Laminex® FR MDF panels must not be subjected to submersion or continuous permanent contact with water. Do not use in saunas or steam rooms.

Surround by Laminex® FR MDF panels are not intended for use as a wall bracing panel.

Surround by Laminex® FR MDF panels are not suitable for any cabinetry, ceiling or flooring applications.

Surround by Laminex® FR MDF **is not** fire rated as part of a fire protected boundary or fire wall.

## Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Surround by Laminex® Fabrication and Installation Manual	Edition 4.0 03.23	<a href="#">Click here</a>
Surround by Laminex® Brochure	03.23	<a href="#">Click here</a>
Surround by Laminex® Design and Specification Guide	03.23	<a href="#">Click here</a>
Surround by Laminex® Warranty	Edition 3.0 03.23	<a href="#">Click here</a>
Surround by Laminex® Fire Certificate	FAS210127 R1.1	<a href="#">Click here</a>
Surround by Laminex® Green Tag	6 April 2023	<a href="#">Click here</a>
Surround by Laminex® SDS	2.1.1.1 - 16.03.2021	<a href="#">Click here</a>
Surround by Laminex® FR MDF Technical Data Sheet (TDS)	Edition 3.0 03.2021	<a href="#">Click here</a>

## Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Laminex Group Pty Limited, trading as Laminex – AU or The Laminex Group.
Manufacturer address for service	332 Bay Rd Cheltenham Victoria 3192 Australia
Manufacturer website	www.laminex.com.au
Manufacturer NZBN	N/A
Manufacturer email	supportservices@laminex.com.au
Manufacturer phone number	+61 132 136

Importer location	New Zealand
Legal and trading name of Importer	Fletcher Building Products Limited (company number 952008), trading as Laminex® NZ.
Importer address for service	810 Great South Road Penrose Auckland 1061 New Zealand
Importer website	www.laminex.co.nz
Importer NZBN	9429037626969
Importer email	CSC@laminex.co.nz
Importer phone number	0800 303 606

## Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

**No**

---